
ARMOR-GARD® BALPCL55 BALLISTICS SECURITY GLASS CLAD POLYCARBONATE



PRODUCT DESCRIPTION

- Bullet Resistant Security Glazing
- Nominal Thickness: 2.308"
- Weight: 27.0 lbs per SF
- Available sizes Any size up to maximum 48" x 72"
- Bullet Resistant Security
 Glazing is available in various
 tints, reflective and high
 transmission designs per
 specifier requirements.
- Lo-Spall designs utilize glass on both surfaces, improving scratch resistance from user abuse.

PERFORMANCE

- 1 Shot 30-06 166 gr AP M2 -NIJ STD 0108.01 Level IV
- Witness Panel 202T43
 Aluminum 6.00" behind tested specimen
- Testing performed by H.P. White Laboratories, Street, MD
- Test Report 7566-04A, dated March 1998

Offering innovative solutions for bullet, blast, impact and wind resistance.

GUIDE SPECIFICATION

Ballistic resistant glass where shown shall be BALPCL55 glass-clad polycarbonate as manufactured by Global Security Glazing, Selma, AL 1-800-640-6541. BALPCL products are designed for applications where ballistics performance is primary and optical characteristics are secondary.

Each unit shall have a nominal overall thickness of 2.308".

APPLICABLE STANDARDS

- NIJ Standard 0108.01
- HPW-TP-0500.01
- ASTM C 1036-06

INSTALLATION

Follow recommended glazing installations as set forth in:

- Glass Association of North America Glazing Manual
- Glass Association of North America Sealant Manual
- Opening Any size up to max. sheet size
- Rabbet Depth 1 ¼"
- Edge Engagement 1"
- Edge Clearance ¼"
- Face Clearance 1/8" each face

WARRANTY (SHORT VERSION)

Global Security Glazing warrants BALPCL Series of glass clad polycarbonate against defects in material and workmanship resulting in edge separation or delamination for a period of five (5) years from date of manufacture. (See Warranty Sheet for complete warranty information and specifications).

 $\begin{array}{l} \text{ARMOR-GARD}^{\circledast} \text{ is either a registered} \\ \text{trademark or trademark of Global} \\ \text{Security Glazing.} \end{array}$

Unless otherwise agreed to in a document signed by both parties, any sale of products by Insulgard™ Security Products ("Insulgard") is made exclusively under Insulgard's Standard Terms and Conditions of Sale, which are available at www.insulgard.com. Insulgard makes no warranty, express or implied, with respect to customer's application outside of the Insulgard Limited Warranty. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Insulgard's Standard Terms Conditions of Sale, the Insulgard Limited Warranty, or this disclaimer, unless any such modification is specifically agreed to in a writing signed by Insulgard. No statement contained herein concerning a possible or suggested use infelled property right of SABIC Innovative Plastics US LLC or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

