
SURE-GARD[®] ICGCP916 GLASS CLAD POLYCARBONATE



PRODUCT DESCRIPTION

- Detention Security Glazing
- Thickness .532"-.638"
- Weight 5.1 lbs per SF
- Available sizes Any size up to maximum 60" x 96"

PERFORMANCE

- H.P. White HPW-TP-0500.02 Forced Entry Level 1 (Report WJE 972491)
- H.P. White HPW-TP-0500.02 Ballistics Level A (Report HPW 7305-04D)
- ASTM F 1915-03 Security Grade 4

Offering innovative solutions for bullet, blast, impact and wind resistance.

GUIDE SPECIFICATION

Security glass where shown shall be ICGCP916 glass-clad polycarbonate as manufactured by Global Security Glazing Selma, AL 1-800-640-6541.

Each unit shall have a nominal overall thickness of 0.570" comprised of:

- ½" heat strengthened or chemically strengthened glass
- ¹/₄" polycarbonate core
- ½" heat strengthened or chemically strengthened glass

Laminated together by urethane laminating interlayer film.

The specified glazing material for this glass type shall meet the following specifications.

APPLICABLE STANDARDS

- H.P. White HPW-TP-0500.02
- ASTM C 1349-04
- ASTM C 1048-04
- ASTM C 1036-06
- ASTM F 1915-03

INSTALLATION

Follow recommended glazing installations as set forth in:

- Glass Association of North America Glazing Manual
- Glass Association of North America Sealant Manual
- Opening: Any size up to max. sheet size
- Rabbet Depth 1 ¼"
- Edge Engagement 1"
- Edge Clearance 1/4"
- Face Clearance 1/8" each face

WARRANTY (SHORT VERSION)

Global Security Glazing warrants ICGCP Series of glass clad polycarbonate against defects in material and workmanship resulting in edge separation or delamination for a period of five (5) years from date of manufacture. (See Warranty Sheet for complete warranty information and specifications).

SURE-GARD[®] is either a registered trademark or trademark of Global Security Glazing.

Unless otherwise agreed to in a document signed by both parties, any sale of products by Insulgard[™] Security Products ("Insulgard") is made exclusively under Insulgard's Standard Terms and Conditions of Sale, which are available at www.insulgard.com. Insulgard makes no warranty, express or implied, with respect to customer's application outside of the Insulgard limited Warranty. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Insulgard's Standard Terms Conditions of Sale, the Insulgard Limited Warranty, nor this disclaimer, unless any such modification is specifically agreed to in a writing signed by Insulgard. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of SABIC Innovative Plastics US LLC or any of its subsidiaries or affiniates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right of SABIC Innovative Plastics US



Insulgard[™] is a trademark of SABIC Innovative Plastics IP B.V.

www.insulgard.com

Phone: (800) 624-6315