

SV TRANSACTION WINDOW



Offering innovative solutions for bullet, blast, impact and wind resistance.

FEATURES

- Rated for Threat Levels 1, 2 or 3 based on UL752 standards
- Natural voice transmission system
- Stainless steel voice rails
- Stainless steel or solid surface deal tray
- Delivered assembled and ready for installation
- High pressure laminate, stainless steel or solid surface base

PRODUCT DESCRIPTION

Insulgard's SV Transaction Window can be manufactured to help protect against Threat Level 1, 2 or 3 based on UL752 Ballistic Standards. Depending on the application, a single window may be used or multiple windows can be arranged together to create several workstations. This transaction window can be used outdoors for a variety of applications.

CONSTRUCTION

Window Construction

- Stainless steel voice tubes surround the vertical edges of bullet resistant glazing material.
- Glazing is affixed to voice tubes at the top and bottom with side separation for natural voice transmission.
- Voice tubes are armored with bullet resistant material consistent with the threat level.
- Glazing is wrapped with anodized aluminum channels.

Window Glazing

- Glazing materials can meet Threat Level 1, 2 or 3 per UL752 Ballistic Standards
- Bullet resistant protection levels are specified by the end user and consistent with the threat level.

UL752 Ballistic Rating Options

- Level 1: 1 1/4" Acrylic
3/4" Lexgard® MP750
- Level 2: 1" Lexgard® MP1000
1 3/8" Acrylic
- Level 3: 1 1/4" Lexgard® SP1250
BALULN25 Armor-Gard®

Voice Rails

Stainless steel (standard)

Countertop/Base

- High pressure plastic laminate (standard)
- Stainless steel or solid surface (optional)
- Base is armored with bullet resistant material consistent with the threat level.

Lexgard® and Armor-Gard® are either registered trademarks or trademarks of Global Security Glazing.

APPLICATIONS

- Cash payment windows
- Ticket windows
- Reception/Interview windows

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

STANDARD SIZES

- 29" x 40"
- 48" x 42"
- 60" x 42"
- 72" x 42"

Custom sizes available upon request.

INSTALLATION DETAILS

Rough opening should be 1/2" wider and 1/4" higher than the size of the unit ordered.

1. Cut a finished opening in the wall sized to accept the standard SV Window.
2. Place preframed SV Window in opening, shim as necessary and attach sides to existing wall with screws, using anchors if the wall is masonry.
3. Apply finish trim molding obtained locally, and installation is complete.

RELATED PRODUCTS

- Pass-through box or package exchanger: Insulgard SVPT Transaction Window
- 3-sided voice rail frame: Insulgard SVT Transaction Window

NOTE

Component ratings are available upon request.

Unless otherwise agreed to in a document signed by both parties, any sale of products by Insulgard™ Security Products ("Insulgard") is made exclusively under Insulgard's Standard Terms and Conditions of Sale, which are available at www.insulgard.com. Insulgard makes no warranty, express or implied, with respect to customer's application outside of the Insulgard Limited Warranty. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Insulgard's Standard Terms Conditions of Sale, the Insulgard Limited Warranty, or this disclaimer, unless any such modification is specifically agreed to in a writing signed by Insulgard. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of SABIC Innovative Plastics US LLC or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Insulgard™ is a trademark of SABIC Innovative Plastics IP B.V.

Insulgard™
SECURITY PRODUCTS

www.insulgard.com

Phone: (800) 624-6315