

# PE PACKAGE PASSER



Offering innovative solutions for bullet, blast, impact and wind resistance.

## FEATURES

- Level 1, 2 and 3 ballistic glazing options based on UL752 standards
- Standard black laminate base
- Automatic door closers
- Allows only one door to be opened at a time
- Full vision through passer
- Wide range of sizes available
- Delivered assembled and ready for installation

## PRODUCT DESCRIPTION

The PE Package Passer is designed to help defeat ballistic assaults from Levels 1, 2 and 3 handguns based on UL752 standards. Interlocking mechanisms keep one door locked at all times while allowing packages to be passed through the full vision barrier without a breach of security. When installed within a glazed window, the full vision unit will not obstruct the windows line of sight.

## CONSTRUCTION

- The PE Package Passer is boxed shaped and constructed from bullet resistant transparent acrylic or polycarbonate material.
- Hinged doors are controlled by a mechanical interlocking mechanism which allows only one door to be opened at a time.
- The standard base is constructed from particle board with a black plastic laminate covering.
- The unit is assembled using 1/4-20 steel machine screws.

## Glazing

- The glazing materials used are consistent with Underwriter Laboratories' Standard 752 specified for bullet resistance.
- Bullet resisting protection level shall be as specified by end user and consistent with threat level.

## UL752 Ballistic Rating Options

- UL Level 1: 1 1/4" Acrylic
- UL Level 2: 1 3/8" Acrylic
- UL Level 3: 1 1/4" Lexgard® SP1250

## APPLICATIONS

This passer is designed to help provide protection for areas that may be subject to ballistic attacks such as:

- Financial institutions
- Convenience stores
- Pharmacies
- Food service establishments
- Law enforcement facilities
- Parcel passer locations
- Other "at risk" facilities

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

## STANDARD SIZES

Outside Dimensions

- Standard: 14" W x 14" H x 14" D
- Large: 16" W x 14" H x 14" D
- Maximum OD Size: 18" W x 18" H x 18" D

Custom sizes may be manufactured based on maximum package dimensions.

## NOTE

This unit was not tested as an assembled product. Only specific items are tested or rated.

Component ratings are available upon request.

Lexgard® is a registered trademark of Global Security Glazing.

Unless otherwise agreed to in a document signed by both parties, any sale of products by Insulgard™ Security Products ("Insulgard") is made exclusively under Insulgard's Standard Terms and Conditions of Sale, which are available at [www.insulgard.com](http://www.insulgard.com). Insulgard makes no warranty, express or implied, with respect to customer's application outside of the Insulgard Limited Warranty. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Insulgard's Standard Terms Conditions of Sale, the Insulgard Limited Warranty, or this disclaimer, unless any such modification is specifically agreed to in a writing signed by Insulgard. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of SABIC Innovative Plastics US LLC or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Insulgard™ is a trademark of SABIC Innovative Plastics IP B.V.

**Insulgard™**  
**SECURITY PRODUCTS**

[www.insulgard.com](http://www.insulgard.com)

Phone: (800) 624-6315