LARGE PACKAGE PASSER



FEATURES

- Level 1, 2 and 3 ballistic glazing options based on UL752 standards
- Constructed with UL Listed bullet resisting materials
- Mechanically interlocking vertical lifting doors
- Completely fabricated with minimal field assembly required
- Custom sizes available
- Designed to pass items up to 24" x 22" x 26"
- Full vision through passer

PRODUCT DESCRIPTION

The PE Package Passer is designed to help defeat ballistic assaults from Levels 1, 2 and 3 handguns based on UL752 standards. Interlocking mechanisms keep one door locked at all times while allowing packages to be passed through the full vision barrier without a breach of security. Designed to be installed with a new or retrofit security barrier or by itself in a finished opening.

Offering innovative solutions for bullet, blast, impact and wind resistance.

CONSTRUCTION

- The Large Package Passer is a box construction using bullet resistant transparent acrylic or polycarbonate material and ballistic aluminum. Full height jambs which house a steel counterweight system for vertical lifting doors.
- Unit will rest on existing or new countertop. No base is supplied.
- Chrome or acrylic lifting handles on lifting doors.
- This passer is held together with extruded clear anodized aluminum and plated steel fasteners to match.

Glazing

- The glazing materials used are consistent with Underwriter Laboratories' Standard 752 specified for bullet resistance.
- Bullet resisting protection level shall be as specified by end user and consistent with threat level.

UL752 Ballistic Rating Options

- UL Level 1: 1 ¼" Acrylic UL Level 2: 1 ¾" Acrylic
- UL Level 3: 1 1/4" Lexgard® SP1250

APPLICATIONS

- Financial institutions
- Convenience stores
- **Pharmacies**
- Food service establishments
- Law enforcement facilities
- Parcel passer locations
- **USPO** stations
- Other "at risk" facilities

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

STANDARD SIZES

Outside Dimensions

- 24" W x 48" & 60" H x 32" D
- 30" W x 48" & 60" H x 32" D
- 39 1/2" W x 48" H x 32" D
- 39 1/2" W x 60" H x 32" D

Custom sizes may be manufactured based on maximum package dimensions.

NOTE

This unit was not tested as an assembled product. Only specific items are tested or rated.

Component ratings are available upon request.

Lexgard® is either a registered trademark or trademark of Global Security Glazing.

Unless otherwise agreed to in a document signed by both parties, any sale of products by Insulgard™ Security Products ("Insulgard") is made exclusively under Insulgard's Standard Terms and Conditions of Sale, which are available at www.insulgard.com. Insulgard makes no warranty, express or implied, with respect to customer's application outside of the Insulgard Limited Warranty. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Insulgard's Standard Terms Conditions of Sale, the Insulgard Limited Warranty, or this disclaimer, unless any such modification is specifically agreed to in a writing signed by Insulgard. No statement contained herein concerning a possible or suggested use infelled property right of SABIC Innovative Plastics US LLC or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.



Insulgard™ is a trademark of SABIC Innovative Plastics IP B V

www.insulgard.com

Phone: (800) 624-6315