

## BULLETBLOCK™ 44/450 BULLET RESISTANT WINDOW SYSTEM





### FRAME DIMENSIONS

- 41/2" framing system
- Head, jamb, sill, mullion and intermediate 2½" x 4½"

# Innovative window solutions for ballistic protection

#### PRODUCT DESCRIPTION

THIS WINDOW SYSTEM IS DESIGNED AND TESTED TO PROVIDE PROTECTION TO AREAS THAT MAY BE SUBJECT TO BALLISTIC ATTACK.

#### **FEATURES**

- Meets UL752 levels 1-3 bullet resistance
- Accepts various glazing materials from 3/4" through 13/8"
- Anodized or painted finishes
- Completely fabricated and shipped fully assembled for easy installation
- Designed for conventional installation and glazing methods

#### **TESTING / CERTIFICATION**

 Tested and listed by UL for bullet resistance meeting UL752 levels 1, 2 and 3.
Proof of testing can be found at www.ul.com under on-line listings

#### CONSTRUCTION

- Components to be constructed from extruded aluminum 6061-T6 alloy temper or equivalent
- Fasteners to be stainless steel type 302 or 304
- Interior/Exterior glazing gaskets to be EPDM sponge and wedge
- All joints and connections will be tight, providing hairline joints and true alignment of adjacent members.
- Weep design to allow for water to exit the exterior at the sill
- · Anchors to be fully concealed

#### **APPLICATIONS**

- Law Enforcement
- Schools
- Government Buildings
- · Corporate Headquarters
- Financial Institutions
- Convenience Stores
- Customer Service Centers

\*Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.



