

BULLETBLOCK™ 44/600 BULLET RESISTANT WINDOW SYSTEM





FRAME DIMENSIONS

- 6" framing system
- Head, jamb, sill, mullion and intermediate 2½" x 6"

Innovative window solutions for ballistic protection

PRODUCT DESCRIPTION

THIS WINDOW SYSTEM IS DESIGNED AND TESTED TO PROVIDE PROTECTION TO AREAS THAT MAY BE SUBJECT TO BALLISTIC ATTACK.

FEATURES

The materials, products, and services of insuloard TM Security Products, its subsidiaries and affiliates ("Seller") are sold subject to Seller's standard conditions of sale, which can be found at www.polymershapes.com and are available upon

- Meets UL752 levels 1-3 bullet resistance
- Accepts various glazing materials from 3/4" through 13/8"
- Anodized or painted finishes
- Completely fabricated and shipped fully assembled for easy installation
- Designed for conventional installation and glazing methods

TESTING / CERTIFICATION

 Tested and listed by UL for bullet resistance meeting UL752 levels 1, 2 and 3.
Proof of testing can be found at www.ul.com under on-line listings

CONSTRUCTION

- Components to be constructed from extruded aluminum 6061-T6 alloy temper or equivalent
- Fasteners to be stainless steel type 302 or 304
- Interior/Exterior glazing gaskets to be EPDM sponge and wedge
- All joints and connections will be tight, providing hairline joints and true alignment of adjacent members.
- Weep design to allow for water to exit the exterior at the sill
- · Anchors to be fully concealed

APPLICATIONS

- Law Enforcement
- Schools
- Government Buildings
- · Corporate Headquarters
- Financial Institutions
- Convenience Stores
- Customer Service Centers

*Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.



