


# **LEXGARD**<sup>®</sup> **MP1000**





### **TECHNICAL DATA**

- Nominal Thickness: 1.031"
- Thickness Tolerance: .93" / 1.134"
- Weight: 6.41 lbs per SF
- Available Sizes: 12" x 12" Minimum
- 72" x 96" Maximum
- Light Transmittance: 59%
- U-Value: .59
- SHGC: .75
- Shading Coefficient: .86
- Available in bronze, gray and green tint

# Innovative glazing solutions for ballistic protection

# **PRODUCT DESCRIPTION**

LEXGARD MP1000 LAMINATED POLYCARBONATE GLAZING HAS BEEN TESTED AND CERTIFIED TO MEET UL 752 LEVEL 2 BALLISTICS PERFORMANCE.

# PERFORMANCE

- .357 Magnum Jacketed with Lead Soft Point
- UL 752 Level 2 UL Listed BP844
- No Spall, No Penetration
- H.P. White HPW-TP-0500.02 Forced Entry Level 4
- ASTM F1233 Class 5

## **GUIDE SPECIFICATION**

Ballistic resistant glass where shown shall be Insulgard's Lexgard MP1000 Laminated Polycarbonate. Each unit for glass type \_\_\_\_ shall be Lexgard MP1000. Lexgard Products are designed for applications where ballistics performance is primary and optical characteristics are secondary. Protected side of window is a mar resistant polycarbonate with threat side a glass surface.

### INSTALLATION

When used for ballistic protection, glazing should be installed in a UL Level 2 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.

Recommended Clearance:

- Face: 1/8" per side
- Edge: 1/4"
- Bite: 1"



Projects and servare entire registrate trademinans on trademinans or optimical registrates of polarical registrates ("Seller") are sold subject to Seller's standard conditions of sale, which can be found at www.polymershapes.com and are available upon request. Although any information or recommendation contained herein is given in good faith, Seller makes no warranty or guarantee, express or implied, () that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating seller's products, services or recommendations. Except as provided in Seller's standard conditions of sale, Seller shall not be responsible for any loss resulting from any use of the other encountering and the interpretation of the second secon

