


LEXGARD® MP750



TECHNICAL DATA

• Nominal Thickness: .766"

• Thickness Tolerance: .69" / .842"

• Weight: 4.76 lbs per SF

· Available Sizes: 12" x 12" Minimum 72" x 96" Maximum

• Light Transmittance: 81%

• U-Value: .72 • SHGC: .80

• Shading Coefficient: .91

· Available in bronze, gray and green tint

Innovative glazing solutions for ballistic protection

PRODUCT DESCRIPTION

LEXGARD MP750 LAMINATED POLYCARBONATE GLAZING HAS BEEN TESTED AND CERTIFIED TO MEET UL 752 LEVEL 1 BALLISTICS PERFORMANCE.

PERFORMANCE

- 3 shots 9mm Full Metal Copper Jacket with Lead Core
- UL 752 Level 1 UL Listed BP844
- No Spall, No Penetration

GUIDE SPECIFICATION

Ballistic resistant glass where shown shall be Insulgard's Lexgard MP750 Laminated Polycarbonate. Each unit for glass type _ shall be Lexgard MP750. Lexgard Products are designed for applications where ballistics performance is primary and optical characteristics are secondary. Protected side of window is a mar resistant polycarbonate with threat side a glass surface.

INSTALLATION

Glazing must be installed in aUL Level 1 Bullet Resistant frame system. Holes must be covered with a UL listed device. All glazing should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.

Recommended Clearance:

- Face: 1/8" per side
- Edge: 3/8"
- Bite: 1"



