


ARMOR-GARD® SP412IG



TECHNICAL DATA

- Nominal Thickness 1.954"
- Thickness Tolerance 1.853" / 2.051"
- Weight 17.719 lbs per SF
- Available Sizes Up to 60" x 96"
- Dimensional Tolerance: +/- .250"
- Light Transmittance .67
- U-Value .42
- SHGC: .60

Innovative glazing solutions for ballistic protection

PRODUCT DESCRIPTION

ARMOR-GARD SP412IG INSULATED GLASS CLAD POLYCARBONATE GLAZING HAS BEEN TESTED AND CERTIFIED TO MEET UL 752 LEVEL 4 BALLISTICS PERFORMANCE.

PERFORMANCE

- UL 752 Level 4 UL Listed File BP844
- .30 Caliber Rifle Lead Core Soft Point (.30-06 Caliber)
- No Spall, No Penetration

GUIDE SPECIFICATION

Ballistic resistant glass where shown shall be Insulgard's SP412IG glass-clad polycarbonate. This product is designed for applications where ballistics performance is primary and optical characteristics are secondary. Protected side of window is a mar resistant polycarbonate with threat side a glass surface.

INSTALLATION

Glass must be installed in a UL Level 4
Bullet Resistant frame system. Holes must
be covered with a UL listed device. All glass
should be installed in accordance with the
guidelines set forth in the current edition
of the Glass Association of North America
(GANA) Glazing and Sealant Manuals. Glazing
systems should incorporate a weep system
to allow moisture and water to escape the
glazing channel.

Recommended Clearance:

- Face: 1/8" per side
- Edge: 3/8"
- Bite: 1"

APPLICABLE STANDARDS

- ANSI Z97.1
- CPSC 16 CFR 1201 (Category I and II)
- ASTM C 1036
- ASTM C 1349

