



LARGE PACKAGE PASSER



Innovative Counter Line Solutions for Ballistic Protection

PRODUCT DESCRIPTION

The PE Package Passer is designed to help defeat ballistic assaults from Levels 1, 2 and 3 handguns based on UL752 standards. Interlocking mechanisms keep one door locked at all times while allowing packages to be passed through the full vision barrier without a breach of security. Designed to be installed with a new or retrofit security barrier or by itself in a finished opening.

STANDARD SIZES

- 24" W x 48" & 60" H x 32" D
- 30" W x 48" & 60" H x 32" D
- 39½" W x 48" H x 32" D
- 39½" W x 60" H x 32" D
-

NOTE

This unit was not tested as an assembled product. Only specific items are tested or rated. Component ratings are available upon request.

FEATURES

- Level 1, 2 and 3 ballistic glazing options based on UL752 standards
- Constructed with UL Listed bullet resisting materials
- Mechanically interlocking vertical lifting doors
- Completely fabricated with minimal field assembly required
- Custom sizes available
- Designed to pass items up to 24" x 22" x 26"
- Full vision through passer

APPLICATIONS

- Financial institutions
- Convenience stores
- Pharmacies
- Food service establishments
- Law enforcement facilities
- Parcel passer locations
- USPO stations
- Other "at risk" facilities

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

BOX CONSTRUCTION

- The Large Package Passer is a box construction using bullet resistant transparent acrylic or polycarbonate material and ballistic aluminum. Full height jambs which house a steel counterweight system for vertical lifting doors.
- Unit will rest on existing or new countertop. No base is supplied.
- Chrome or acrylic lifting handles on lifting doors.
- This passer is held together with extruded clear anodized aluminum and plated steel fasteners to match.

GLAZING

- The glazing materials used are consistent with Underwriter Laboratories' Standard 752 specified for bullet resistance.
- Bullet resisting protection level shall be as specified by end user and consistent with threat level.

UL752 BALLISTIC RATING OPTIONS

- UL Level 1: 1¼" Acrylic
- UL Level 2: 1⅜" Acrylic
- UL Level 3: 1¼" Lexgard® SP1250