

PE PACKAGE PASSER





STANDARD SIZES

OUTSIDE DIMENSIONS

- Standard: 14" W x 14" H x 14" D
- Large: 16" W x 14" H x 14" D
- Mazimum OD Size: 18" W x 18" H x 18" D

NOTE

Custom sizes may be manufactured based on maximum package dimensions.

This unit was not tested as an assembled product. Only specific items are tested or rated. Component ratings are available upon request.

Innovative Counter Line Solutions for Ballistic Protection

PRODUCT DESCRIPTION

The PE Package Passer is designed to help defeat ballistic assaults from Levels 1, 2 and 3 handguns based on UL752 standards. Interlocking mechanisms keep one door locked at all times while allowing packages to be passed through the full vision barrier without a breach of security. When installed within a glazed window, the full vision unit will not obstruct the windows line of sight.

FEATURES

- Level 1, 2 and 3 ballistic glazing options based on UL752 standards
- Standard black laminate base
- Automatic door closers
- Allows only one door to be opened at a time
- Full vision through passer
- Wide range of sizes available
- Delivered assembled and ready for installation

APPLICATIONS

This passer is designed to help provide protection for areas that may be subject to ballistic attacks such as:

- Financial institutions
- Convenience stores
- Pharmacies
- Food service establishments
- Law enforcement facilities
- Parcel passer locations
- Other "at risk" facilities

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

CONSTRUCTION

- The PE Package Passer is boxed shaped and constructed froM bullet resistant transparent acrylic or polycarbonate material.
- Hinged doors are controlled by a mechanical interlocking mechanism which allows only one door to be opened at a time.
- The standard base is constructed from particle board with a black plastic laminate covering.
- The unit is assembled using 1/4-20 steel machine screws.

GLAZING

- The glazing materials used are consistent with Underwriter Laboratories' Standard 752 specified for bullet resistance.
- Bullet resisting protection level shall be as specified by end user and consistent with threat level.

UL752 BALLISTIC RATING OPTIONS

- UL Level 1: 11/4" Acrylic
- UL Level 2: 13/8" Acrylic
- UL Level 3: 1¼" Lexgard® SP1250

The materials, products, and services of InsulgradTM Security Products, its subsidiaries and affiliates ("Seller") are sold subject to Seller's standard conditions of sale, which can be found at www.polymershapes.com and are available upon request. Although any information or recommendation contained herein is given in good faith, Seller makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, to give as to the effectiveness or salety of any design incorporating sellers products, services or recommendations. Except as provided in Seller's standard conditions of sale, Seller shall not be responsible for making its own determination as to the subsidiaries or trace standard conditions of sale. Seller shall not be responsible for making its own determination as to the subsidiaries of Seller's standard conditions of sale. Seller shall not be responsible for making its own determination as to the subsidiaries of Seller's Standard Conditions of Seller's tabutes its specification user is particular use through appropriate end-use testing and analysis. Nothing in any document shall be deemed to alter or valves and any provision of Seller's Standard Conditions of Seller's Standard Conditions

