

SHURESAFE* SECURITY DRAWER





Innovative Counter Line Solutions for Ballistic Protection

PRODUCT DESCRIPTION

ShureSAFE®'s secure transaction drawers are (level 3) bullet-resistant, UL®-approved, and made entirely from stainless steel resulting in strong, dependable security.

STANDARD SIZES

- Overall: 24" W x 10" H x 28" D
- Frame Face: 24" W x 1011/16"
- Transfer Area: 13¾" W x 61⁄8" H 103⁄8" D
- Wall Opening 24¼" W x 10¼" H
- Weight: 138 lbs

FEATURES

- Removable deal tray to expose larger transfer area for transferring currency bags, gallon-sized containers and bulky products
- Self-opening and closing transaction area cover prevents simultaneous customer and operator access
- Restricts outside airflow and external environment penetration
- Built-in speaker compatible with preexisting commercial intercom systems
- Designed for installation for 41/2" thick walls
- UL® approved Level 3 bullet resistance
- Internal speaker with hands-free intercom

APPLICATIONS

- Pharmacies
- Convenience stores
- Correctional facilities
- Financial institutions
- Check cashing / loan centers
- Law enforcement facilities
- Government facilities
- Other "at risk" facilities

Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

The materials, products, and services of InsulgardTM Security Products, its subsidiaries and affiliates ("Seller") are sold subject to Seller's standard conditions of sale, which can be found at www.polymershapes.com and are available upon request. Although any information or recommendation contained herein is given in good faith, Seller makes no warranty or guarantee, express or implied. (i) that the results described herein will be obtained under end-use conditions. Except as provided in Seller's standard conditions of sale, Seller shall not be responsible for any loss; monotating seller products, services as constrained activations. Except as provided in Seller's standard conditions of selle, Seller Seller to be responsible for any loss; moticity for any loss; motic

