

SLH MANUAL HORIZONTAL SLIDING TRANSACTION WINDOW SYSTEM





Innovative transaction window solutions for ballistic protection

PRODUCT DESCRIPTION

Insulgard's SLH horizontal slider can be constructed from materials designed to help combat ballistic assaults from Level 1, 2 or 3 handguns per UL752 Ballistics Standards. The sliding panel can be opened to allow the passage of packages, contact with customers, and better voice transmission during periods of low threat. If a threat is detected, the sliding panel can be closed and locked. In the locked position the full vision panel still allows for voice transmission and currency exchange.

APPLICATIONS

- Convenience stores
- $\bullet \ \mathsf{Gas} \ \mathsf{stations}$
- Food service establishments
- · Law enforcement facilities
- · Other "at risk" facilities

*Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

FEATURES

- Glazing is rated for Threat Level 1, 2, or 3 based on UL752 Ballistic Standards
- · Wide range of sizes available
- · Variety of finishes available
- Delivered complete and ready for installation
- Fabricated from UL listed bullet resistant glazing material
- Full vision through unit

CONSTRUCTION

The SLH horizontal slider consists of fixed and sliding transparent bullet resistant panels to secure an opening, along with the aluminum framework, hardware, and fasteners needed for installation.

Glazing

Glazing materials can be rated for Threat Level 1, 2 or 3 per UL752 Ballistics Standards.

UL752 Ballistic Rating Options

Level 1: 1¼" AcrylicLevel 2: 1¾" Acrylic

• Level 3: 11/4" Lexgard® SP1250

Finishes

- Clear anodized
- Dark bronze anodized
- Painted aluminum

Frame

- •1¾" x 4" aluminum tube jambs and head
- Glazing channel surrounds the bullet resistant fixed panel



