

SLV MANUAL VERTICAL SLIDING TRANSACTION WINDOW SYSTEM





APPLICATIONS

- Convenience stores
- Gas stations
- Food service establishments
- Financial Institutions
- · Law enforcement facilities
- Other "at risk" facilities

*Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

Innovative transaction window solutions for ballistic protection

PRODUCT DESCRIPTION

Insulgard's bullet resistant SLV vertical slider can be constructed from materials designed to help combat ballistic assaults from Level1, 2 or 3 handguns per UL752 Ballistics Standards. The manual lift sliding panel can be opened to allow the passage of packages, contact with customers, and better voice transmission during periods of low threat. If a threat is detected, the vertical panel can be closed and locked. In the locked position the full vision panel still allows for voice transmission and currency exchange.

CONSTRUCTION

The SLV vertical slider consists of fixed and sliding transparent bullet resistant panels to secure an opening, along with the aluminum framework, hardware, and fasteners needed for installation.

Manual and automatic locking options are available.

Glazina

Glazing materials can be rated for Threat Level 1, 2 or 3 per UL752 Ballistics Standards.

UL752 Ballistic Rating Options

Level 1: 1¼" AcrylicLevel 2: 1¾" Acrylic

• Level 3: 11/4" Lexgard® SP1250

Finishes

- Clear anodized
- · Dark bronze anodized
- Painted aluminum

Frame

- Aluminum jambs house a steel counter balance for ease of operation. For larger units, jamb size: 3" x 9"
- Aluminum head houses a clock spring type overhead counterbalance system. For smaller units, jamb size: 2½" x 4½"

FEATURES

- Glazing is rated for Threat Level 1, 2, or 3 based on UL752 Ballistic Standards
- · Variety of finishes available
- Delivered complete and ready for installation
- Fabricated from UL listed bullet resistant glazing material
- Full vision through unit
- Manual lift operation

