



# SVPT TRANSACTION WINDOW



## Innovative transaction window solutions for ballistic protection

### PRODUCT DESCRIPTION

Insulgard's SVPT Transaction Window can be manufactured help protect against threat Level 1, 2 or 3 based on UL752 Ballistic Standards. A single unit can be used in applications such as cash payment or reception windows. Multiple units can be grouped together to create several workstations for applications such as ticket sales. This model also features a bullet resistant package exchange unit which allows bulk items to be passed through without breaching security.

### STANDARD SIZES

- 29" x 40"
- 48" x 42"
- 60" x 42"
- 72" x 42"
- Custom sizes available upon request

### FEATURES

- Glazing is rated for Threat Levels 1, 2 or 3 based on UL752 standards
- Natural voice transmission system
- Stainless steel voice rails
- Stainless steel or solid surface deal tray
- Delivered assembled and ready for installation
- High pressure laminate, stainless steel or solid surface base
- Package exchange unit for bulk items

### APPLICATIONS

- Cash payment windows
- Ticket windows
- Reception / Interview windows

\*Each end user should determine their ballistic threat and identify the appropriate product(s) to resist that threat.

### CONSTRUCTION

#### Window Construction

- Stainless steel voice tubes surround the vertical edges of bullet resistant glazing material.
- Glazing is affixed to voice tubes at the top and bottom with side separation for natural voice transmission.
- Voice tubes are armored with bullet resistant material consistent with the threat level.
- Glazing is wrapped with anodized aluminum channels.

#### Window Glazing

- Glazing materials can meet Threat Level 1, 2 or 3 per UL752 Ballistic Standards
- Bullet resistant protection levels are specified by the end user and consistent with the threat level.

#### UL752 Ballistic Rating Options

- Level 1: 1¼" Acrylic  
¾" Lexgard® MP750
- Level 2: 1" Lexgard® MP1000  
1⅜" Acrylic
- Level 3: 1¼" Lexgard® SP1250  
BALULN25 Armor-Gard®

#### Voicerrails

- Stainless steel (standard)

#### Countertop/Base

- High pressure plastic laminate (standard)
- Stainless steel or solid surface (optional)
- Base is armored with bullet resistant material consistent with the threat level.

### INSTALLATION DETAILS

Rough opening should be ½" wider and ¼" higher than the size of the unit ordered.

1. Cut a finished opening in the wall sized to accept the standard SVPT Window.
2. Place preformed SVPT Window in opening, shim as necessary and attach sides to existing wall with screws, using anchors if the wall is masonry.
3. Apply finish trim molding obtained locally, and installation is complete.