

## TOR-GARD® 30



## Innovative glazing solutions for tornado and hurricane protection.

### PRODUCT DESCRIPTION

TOR-GARD® 30 GLAZING WAS TESTED IN THE STORMDEFEND TTH350 DOOR SYSTEM WHICH IS CERTIFIED, LISTED AND LABELED FOR USE IN TORNADO AND HURRICANE SAFE ROOMS/STORM SHELTERS MEETING **FEMA P361-15** AND **ICC500-2014** STANDARDS.

### TECHNICAL DATA

- Nominal Thickness 1.286"
- Dimensional Tolerance +/- .250"
- Maximum sheet size 60" x 96"
- Weight 10.84#/sqft
- Light transmittance 65%
- U-Value .58
- Solar Heat Gain Coefficient .67
- Shading Coefficient .78

### PERFORMANCE TESTING

- FEMA P361-15
- ICC500-2014
- UL752 Level 3 Bullet Resistance

### OPTIONS

- Tinted Glazing
- Translucent Interlayers

### INSTALLATION

- Glazing to be installed in accordance with the guidelines set forth in the current edition of the GANA Glazing and Sealant Manuals.

### WARRANTY (SHORT VERSION)

- Global Security Glazing warrants TOR-Tard® Series of glass clad polycarbonate against defects in material and workmanship resulting in edge separation or delamination for a period of five (5) years from date of manufacture.

*(See Warranty Sheet for complete warranty information and specifications).*